

acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

SECTION 1: Identification

1.1 Product identifier

Trade name

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

primer

WELD-ALL 8155 PURPLE PRIMER

1.3 Details of the supplier of the safety data sheet

Weld-All, LLC 100 Trousdale Way, Hartsville, TN 37074 United States

Telephone: (305) 755-3615

1.4 Emergency telephone number

Emergency information service

24 Hours: CHEMTEL Tel. 800.255-3924, +1 813-248-0585 (International)

Date of compilation: 2022-05-05

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Hazard class	Category
acute toxicity (oral)	4
acute toxicity (inhal.)	4
skin corrosion/irritation	2
serious eye damage/eye irritation	2
specific target organ toxicity - single exposure (respiratory tract irritation)	3
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3
flammable liquid	2

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger
- Pictograms

GHS02, GHS07





acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

- Hazard statements	
H225	Highly flammable liquid and vapor.
H302+H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
- Precautionary statem	nents
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
P301+P312	If swallowed: Call a poison center/doctor if you feel unwell.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

cyclohexanone, methyl ethyl ketone, acetone

2.3 Other hazards

Hazards not otherwise classified

Contains proprietary additive. May produce an allergic reaction.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
cyclohexanone	CAS No 108-94-1	25 - < 50	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Flam. Liq. 3 / H226
methyl ethyl ketone	CAS No 78-93-3	25 - < 50	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225
acetone	CAS No 67-64-1	10-<25	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225
proprietary additive	CAS No 81-48-1	<1	Skin Sens. 1B / H317

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

Flash point

1.4 °F

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	cyclohexanone	108-94-1	PEL (CA)	25	100						Cal/ OSHA PEL
US	cyclohexanone	108-94-1	REL	25 (10 h)	100 (10 h)						NIOSH REL
US	cyclohexanone	108-94-1	PEL	50	200						29 CFR 1910.100 0
US	cyclohexanone	108-94-1	TLV®	20		50				Н	ACGIH® 2022
US	acetone	67-64-1	PEL (CA)	500	1,200	750	1,780	3,000			Cal/ OSHA PEL
US	acetone	67-64-1	REL	250 (10 h)	590 (10 h)						NIOSH REL
US	acetone	67-64-1	TLV®	250		500					ACGIH® 2022
US	acetone	67-64-1	PEL	1,000	2,400						29 CFR 1910.100 0
US	2-butanone	78-93-3	REL	200 (10 h)	590 (10 h)	300	885				NIOSH REL
US	2-butanone (methyl ethyl ketone)	78-93-3	PEL	200	590						29 CFR 1910.100 0
US	methyl ethyl ketone	78-93-3	TLV®	200		300					ACGIH® 2022
US	methyl ethyl ketone (MEK) (2- butanone) (ethyl methyl ketone)	78-93-3	PEL (CA)	200	590	300	885				Cal/ OSHA PEL

Notation

Н

ceiling value is a limit value above which exposure should not occur absorbed through the skin Ceiling-C

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period STEL (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified TWA



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Biological limit values Country Name of agent Parameter Notation Identifier Value Source US cyclohexanone 1,2-cyclohexanediol hydr BEI® 80 mg/l ACGIH® 2022 US cyclohexanone cyclohexanol hydr BEI® 8 mg/l ACGIH® 2022 25 mg/l US acetone acetone BEI® ACGIH® 2022 US methyl ethyl ketone BEI® 2 mg/l ACGIH® 2022 methyl ethyl ketone

Notation hydr

hydrolysis

Relevant DNELs of components of the mixture							
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time	
cyclohexanone	108-94-1	DNEL	10 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects	
cyclohexanone	108-94-1	DNEL	20 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects	
cyclohexanone	108-94-1	DNEL	10 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects	
cyclohexanone	108-94-1	DNEL	20 mg/m ³	human, inhalatory	worker (industry)	acute - local effects	
cyclohexanone	108-94-1	DNEL	4 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic ef- fects	
cyclohexanone	108-94-1	DNEL	4 mg/kg bw/ day	human, dermal	worker (industry)	acute - systemic ef- fects	
methyl ethyl ketone	78-93-3	DNEL	600 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects	
methyl ethyl ketone	78-93-3	DNEL	1,161 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects	
acetone	67-64-1	DNEL	1,210 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects	
acetone	67-64-1	DNEL	2,420 mg/m ³	human, inhalatory	worker (industry)	acute - local effects	
acetone	67-64-1	DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects	

Relevant PNECs of components of the mixture								
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental com- partment	Exposure time		
cyclohexanone	108-94-1	PNEC	0.356 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)		
cyclohexanone	108-94-1	PNEC	0.036 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)		



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Relevant PNECs of components of the mixture								
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental com- partment	Exposure time		
cyclohexanone	108-94-1	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)		
cyclohexanone	108-94-1	PNEC	2.69 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)		
cyclohexanone	108-94-1	PNEC	0.269 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)		
cyclohexanone	108-94-1	PNEC	0.328 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)		
methyl ethyl ketone	78-93-3	PNEC	55.8 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)		
methyl ethyl ketone	78-93-3	PNEC	55.8 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)		
methyl ethyl ketone	78-93-3	PNEC	709 ^{mg} /l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)		
methyl ethyl ketone	78-93-3	PNEC	284.7 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)		
methyl ethyl ketone	78-93-3	PNEC	284.7 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)		
methyl ethyl ketone	78-93-3	PNEC	22.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)		
acetone	67-64-1	PNEC	10.6 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)		
acetone	67-64-1	PNEC	1.06 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)		
acetone	67-64-1	PNEC	100 ^{mg} /l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)		
acetone	67-64-1	PNEC	30.4 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)		
acetone	67-64-1	PNEC	3.04 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)		
acetone	67-64-1	PNEC	29.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)		

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	violet
Particle	not relevant (liquid)
Odor	pleasant

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	56.05 °C
Flash point	-17 °C
Flash point	1.4 °F
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	240 hPa at 20 °C
Density	0.857 ^g / _{cm³} at 73 °F
Vapor density	this information is not available



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	420 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

VOC content	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: <= 400 g/L.
Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed. Harmful if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
cyclohexanone	108-94-1	oral	500 ^{mg} / _{kg}
cyclohexanone	108-94-1	dermal	1,100 ^{mg} / _{kg}
cyclohexanone	108-94-1	inhalation: vapor	>6.2 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Contains proprietary additive. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans					
CAS No	Classification	Number			
108-94-1	3				
	CAS No	CAS No Classification			

Legend 3

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Specific target organ toxicity - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

101		Date of compliation. 2022-05-0
SECT	ION 14: Transport information	
14.1	UN number	
	DOT	UN 1993
	IMDG-Code	UN 1993
	ICAO-TI	UN 1993
14.2	UN proper shipping name	
	DOT	Flammable liquid, n.o.s.
	IMDG-Code	FLAMMABLE LIQUID, N.O.S.
	ICAO-TI	Flammable liquid, n.o.s.
	Technical name (hazardous ingredients)	acetone, methyl ethyl ketone
14.3	Transport hazard class(es)	
	DOT	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	DOT	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	non-environmentally hazardous acc. to the danger ous goods regulations
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to IMO instruments	
	The cargo is not intended to be carried in bulk.	
	Information for each of the UN Model Regulation	ns
	Transport of dangerous goods by road or rail (49	CFR US DOT) - Additional information
	Particulars in the shipper's declaration	UN1993, Flammable liquid, n.o.s., (acetone, methyl ethyl ketone, solution), 3, II
	Reportable quantity (RQ)	12,500 lbs (5,675 kg) (cyclohexanone) (acetone)
	Danger label(s)	3

IB2, T7, TP1, TP8, TP28

128

ERG No

Special provisions (SP)



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

ersion number: 1.0	Date of compilation: 2022-05-
International Maritime Dangerous	Goods Code (IMDG) - Additional information
Marine pollutant	-
Danger label(s)	3
•	
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, <u>S-E</u>
Stowage category	В
International Civil Aviation Organiz	zation (ICAO-IATA/DGR) - Additional information
Danger label(s)	3
Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methyl ethyl ketone	78-93-3		3 4	5000 (2270)
cyclohexanone	108-94-1		4	5000 (2270)
acetone	67-64-1		4	5000 (2270)

Legend

"3" indicates that the source is section 112 of the Clean Air Act

"4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Δ



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
methyl ethyl ketone	78-93-3		CA TACs OEHHA RELs
acetone	67-64-1		ATSDR Neurotoxicants

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	De Minimis Concen- tration Threshold
methyl ethyl ketone	78-93-3			1.0 %
cyclohexanone	108-94-1			1.0 %
acetone	67-64-1			1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
methyl ethyl ketone	78-93-3	A, N, O	
cyclohexanone	108-94-1	A, N, O	skin
acetone	67-64-1	A, N, O	

Legend

А

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physic-al Agents and Biological Exposure Indices for 1992-93", available from ACGIH National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Trans-Ν fer

0 Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methyl ethyl ketone	78-93-3		F3
cyclohexanone	108-94-1		F2
acetone	67-64-1		F3

Legend F2

Flammable - Second Degree

F3 Flammable - Third Degree



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
2-BUTANONE	78-93-3	E
CYCLOHEXANONE	108-94-1	E
2-PROPANONE	67-64-1	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methyl ethyl ketone	78-93-3	T, F
cyclohexanone	108-94-1	T, F
acetone	67-64-1	T, F

Legend

F Flammability (NFPA®)

Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or resid- ual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
TR	CICR	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2022	From ACGIH®, 2022 TLVs® and BEIs® Book. Copyright 2022. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presenta-tions/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Abbr.	Descriptions of used abbreviations
IMDG-Code	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)



acc. to 29 CFR 1910.1200 App D

WELD-ALL 8155 PURPLE PRIMER

Version number: 1.0

Date of compilation: 2022-05-05

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.